

Leaf, 30kWh (refabrication battery)

Model: ZEO

Battery performance and durability, Article 10, Regulation (EU) 2023/1542

Parameter	Value	Explanation
Rated capacity	56 Ah	Capacity(Ah) is divided energy(Wh) by the nominal battery voltage
Capacity fade	1.5 %	The value indicated relates to maximum decrease in Rated Capacity after 1 years or 20,000 km of normal customer use in European market. This value may vary depending on driving style, charging behavior, and environmental factors. No Warranty implication can be derived from any of the information provided.
Power	125 kW	Available maximum power at SOC80% of initial battery condition at room temperature.
Power fade	0 %	The value indicated relates to maximum decrease in Maximum Power after 1 years or 20,000 km of normal customer use in European market. This value may vary depending on driving style, charging behavior, and environmental factors.
Internal resistance	0.088 Ω	Internal resistance under SOC 80% of initial battery condition.
Internal resistance increase	7.2 %	Maximum increase after 1 years or 20,000km of normal customer use in European market, this increase may vary depending on driving style, charging behavior, and environmental factors.
Energy round trip efficiency	99.31 %	Energy round trip efficiency under new battery condition, this value indicates energy loss during battery discharge and charge process.
Energy round trip efficiency fade	0.027 %	The value indicated relates to maximum decrease in Energy round trip efficiency after 1 years or 20,000 km of normal customer use in European market. This value may vary depending on driving style, charging behavior, and environmental factors.
Expected life-time	1 years 20,000 km	The indicated guide value is based on the period of time or mileage for which the battery manufacturer has evaluated performance fade. Total service life may vary depending on driving style, charging behavior, and environmental factors. No Warranty implication can be derived from any of the information provided.